

SETTING THE STANDARD FOR VARIABLE MESSAGE SIGNS

Smart Messenger

Smart Messenger is ideal for inner city and urban works or for roads with speed zones up to 50mph.

Full colour LED technology

- Displays up to 4 lines of text, up to 11 characters per line (Highway Compliant)
- Full colour RGB display with an 80 x 48 pixel resolution allowing full graphics and text for events, advertising and pedestrian use

Additional Capabilities

- NTIS Journey time capability
- GPS tracking
- Speed radar fitted as standard
- Your speed is displayed
- Speed activated messaging
- Driver feedback messaging

Easy to update

- Via Zephyr, Swarco's simple to use interface
- Ready for MyCity (Urban Mobility Management Software)

Exceeds all standards for Highway deployment

- CE Certified
- Fully conforming to standard BS EN 12966
- Registered under TOPAS 2516D



Key uses:

- + Road and utility works
- + Speed display and driver feedback
- + Highway and construction site safety
- + Public, social and entertainment events
- + Public and safety information
- + Speed restrictions or change in speed limit
- + Parking management, information and direction



E vms@srltraffic.ie **T** 01 862 1093











SETTING THE STANDARD FOR VARIABLE MESSAGE SIGNS

Smart Messenger

Product Specification

| Operating Height | 3319mm |
|------------------|---|
| Travel Height | 2328mm |
| Length | 1923mm |
| Width | 1716mm |
| Weight | 750kg |
| Matrix Display | W1600mm (80 pixels) x H960mm (48 pixels), Full Colour |
| Communication | GPRS / 3G / 4G (Tablet control via Wi-Fi as an option) |
| Power | Battery plus solar |

Access unrivalled service and nationwide coverage 24/7, 365 days a year











